



Part of the Vitaris cleaning system

Destoning and classifying

The combistoner MTCH masters two applications in one single machine. It is an excellent solution for an efficient separation of stones and glass while grading grains and mixed fraction. It is available as a fresh air (FA) version, as a recycled air (RA) version or in combination with MANW. Both recycled air options reducing the energy consumption up to 15%.

Benefits

- Flexible & convenient sieve layer exchange Leads to fast maintenance & higher uptime
- Hygienic production
 Closed design with FDA approved materials
- High separation performance by integrated dust separation and electric airflow control












/ST MTRD MTCH MVSS MVS





The quick-clamping system enables the sieve layer exchange in less than 5 minutes.



Impurities (glass, stones)
Aspiration connection


Vitaris combistoner MTCH


Mastering two applications for excellent selectivity

Overview of technical data:

Model		Capacity (wheat)		
	Cleaning t/h	Motor rating	Weight ka	
MTCH-60	2-12	4	860	
MTCH-120	12 – 24	8	1300	

	Dimensions mm	•
Α	В	С
1340	2470	1410
1980	2470	1490





Examples of combinations in the Vitaris cleaning system is available as fresh air (FA), MANW or recycled air (RA) option





Stand-alone

MTCH-60-FA MTCH-120-FA





Combistoner with

air-recycling aspirator

MTCH-120-FA-MVSS







Combicleaner and air-recycling aspirator with air-recycling aspiration channel

MTKC-60-FA-MVST-MVSS













