


Horizontal flow pack





SA COLONIALY





- RAL 9006 grey painted steel frame with AISI 304 stainless steel guards;
- Longitudinal sealing unit consisting of four pairs of wheels: pulling, re-heating, sealing and sealing flap;
- Rotary transverse sealing unit with one or multiple sealing up-jaw;
- One or double self-centring reel holder. On request automatic splicing;
- Outfeed conveyor 1000 mm long;
- Fixed or adjustable forming tunnel;
- Photocell for printed film;
- Label unit;
- Provision for automatic feeding;
- Photocell for "No Product No Bag";
- Microswitch for end of film;
- Band applicator for easy opening of the package;
- Standard spare parts kit;
- Safety guards in transparent shockproof plastic material.

Type of packaging









Product length	min 30 mm	max 300 mm
Product width	min 10 mm	max 150 mm
Product height	min 1 mm	max 100 mm
Reel holder width	400 mm	
Mechanical speed	up to 800 cycles per minute	
Weight	1000 kg	
Power supply	6 Kw	



Motorization by means of 4 independent Brushless motors




Mechanical speed up to 800 cycles per minute



Voltage 400V / 3 phase Earth + Neutral, 50Hz



Machine conforms to CE regulations































Delfin srl Via G. Keplero, 18 36034 Malo, VI – Italy









