



BELPYCNO

DENSITY PYCNOMETER

FULLY AUTOMATED AND HIGHLY ACCURATE DENSITY MEASUREMENT

part of VERDER scientific

SHORT MEASUREMENT TIME AND FAST SYSTEM STABILIZATION

FULLY AUTOMATED DENSITY MEASUREMENT OF POWDERS AND POROUS MATERIALS

The BELPYCNO L allows the accurate measurement of skeleton density of solids and powders as well as the true density of pastes and liquids. The combination of an internal temperature control and an absolute pressure transducer compensates any influences from ambient temperature and pressure fluctuations.

DETERMINATION OF THE DENSITY OF POWDERS AND POROUS SOLIDS

The BELPYCNO L is a fully automated instrument for the determination of the volume and density of powders, granulates, porous materials, mixtures, pastes and liquids. The BELPYCNO L replaces the classical method of liquid displacement utilizing a probing gas such as Helium which can reach even the smallest pores less than 1 nm diameter. Thus, the density of powders and porous materials can be determined exactly.

THE MEASUREMENT AND CALIBRATION PROCEDURES ARE FULLY AUTOMATED

The BELPYCNO L can work as a standalone instrument or being connected to a computer. The including software offers an easy programming from the computer, reporting and storage of data and analytical results.

In addition, for each measurement step the computed volume and density are displayed in situ.



BENEFITS

- I Built-in linearized absolute pressure transducer
- I Sample cell and reference volumes are separated from the electronics
- I Built-in accurate ATC (Automatic Temperature Control)
- I Short measurement time and fast system stabilization
- I Unrivalled reproducibility of results

ACCURATE DENSITY DETERMINATION FOR VARIOUS APPLICATIONS

The BELPYCNO L pycnometer is equipped with up to 3 reference chamber volumes (approx. 20, 40 and 60 cm³) in order to give the best performance in combination with the chosen sample chamber (approx. 4, 20, 40, 60, 100 and 135 cm³). Independent of ambient temperature and pressure variations, the BELPYCNO L allows measurements which are not limited by time consuming calibration procedures.

Once calibrated the pycnometer carries out the analysis without any concerns. No contamination risks due to gas loading from reference chamber (high pressure) into sample chamber (low pressure), supported by programmable discharge restriction and easy use of paper filters. Variable loading pressure permits the analysis of foams and compressible samples.



FEATURES

BUILT-IN FINE POWDER OPTION

 Programmable discharge restriction and easy use of paper filters to prevent powders dragging by pressure drop, thus reducing maintenance.

GAS LOADING FROM REFERENCE CHAMBER (HIGH PRESSURE) INTO SAMPLE CHAMBER (LOW PRESSURE)

- No contamination of reference chamber with fine powders or condensed liquids.
- Feature of variable loading pressure permits the analysis of foams and compressible samples.

BUILT-IN MULTI VOLUME CAPABILITY

No requirement for instrument modifications.

Easy choice of the best configuration according to sample volume and nature In addition, for each measurement step the computed volume and density are displayed in-situ.

- BUILT-IN LINEARIZED ABSOLUTE PRESSURE TRANSDUCER
- Independent of ambient pressure fluctuations from climate or in low-pressure labs.

SAMPLE CELL AND REFERENCE VOLUMES SEPARATED FROM THE ELECTRONICS

• Unit can be installed in a glove box e.g. for use with radioactive samples.

BUILT-IN ACCURATE ATC (AUTOMATIC TEMPERATURE CONTROL)

- Constant temperature independent of ambient fluctuations
- Maintenance free
- No external thermostat necessary
- Various temperatures possible

TECHNICAL INFORMATION

BELPYCNO

Reference chamber volumes	Approx. 20, 40 and 60 cm ³		
Sample chamber volumes	Approx. 4, 20, 40, 60 , 100 and 150 cm ³		
Probe gas	Helium (other inert gases possible)		
Control	Integrated micro processor		
Keyboard	Alphanumeric foil		
Display	4-line 40 characters LCD-display with back light		
Pre-treatment	Flow, programmable purge cycles optional with vacuum preparation		
Temperature	14°C to 40°C (optional 60°C with external oven) resolution \pm 0.01°C		
Pressure transducer	0.001 kPa displayed resolution		
AD-converter	19 Bit		
Accuracy	0.01%		
Reproducibility	0.01%		
Vacuum connector	KF-10		
Interfaces	2 x serial (external balance, PC-data transfer), 1 parallel (printer)		
Sensor (optional)	Humidity		
Power supply	AC 100 - 240 V (240 W), 50 / 60Hz		
Dimensions (W x H x D), weight	250 mm x 330 mm x 450 mm, 17 kg		

Results at a glance:

Terrenter Terrenter 1,515659 Result Viterater 8,315453	Tercentiae Gurrent (2) Genkers(3) 19,99 0,46 (2,626315		
an an Vitan Car an Car an an Larbor Landour		Anno U (R) Part announ forther a Part announ forther a	el sone ann an 24
Millionnes - Description Comparts Randonest De- generation - An Analysis and the Comparts Analysis and the Comparison Wangle Science - Analysis Wangle Science - Analysis Description - Analysis Description - Analysis - Analysis Bengels - Analysis - Analysis Bengels - Analysis - Analysis	examplement inference (12) ment Twento 11, 20, 20, 20, 20, 20, 20, 20, 20, 20, 20		

MICROTRAC

PARTICLE CHARACTERIZATION

Microtrac Inc. 3230 N. Susquehanna T

Phone: +1 888 643 5880 marketing@microtrac.com

<mark>Microtrac Retsch GmbH</mark> Retsch-Allee 1-5 42781 Haan · Germany

Phone: +49 2104 2333 300 info@microtrac.com

MicrotracBEL Corp.

8-2-52 Nanko Higashi, Suminoe-ku Osaka 559-0031 · Japan

Phone: +81 6 6655 0360 nfo@microtrac-bel.com

Microtrac Formulaction SAS 3-5 rue Paule Raymondis 31200 Toulouse · France

Phone: +33 (0)5 62 89 29 29 contact.fr@mtf.verder.com

www.microtrac.com

part of **VERDER**