

Flight conveyors





General

Ottevanger Milling Engineers flight conveyors are used for applications that have the most strict hygienic demands. The flight conveyors are suitable for conveying practically all powders and granulates. Capacities range from 30 up to 400 m³/h. These conveyors are capable of inclined conveying up to an angle of 40°.

Features

- » S235 steel trough, U-shaped, fully enclosed design
- » primer and paint finish
- » geared drive units
- » product overflow detection is standard
- » chain tensioner
- » guide strips for the flights
- » HMPE flights

Special Executions

- » executed in AISI304
- » executed in galvanized S235 steel
- » double the amount of flights
- » drop bottom
- » speed sensor
- » ATEX22 zoned drive-units
- » inclined installation up to 40° (depending on product)

	Capacity (m³/h)
Туре	0,5 (m/s)
200	40
300	68
400	130
600	270





- » Design » Engineering » Manufacturing » Construction and commissioning
- » Feed mills » Pet food plants » Aqua feed plants » Cereal processing plants
 - » Soybean processing plants » Premix and concentrate plants » Silos
 - » Bulk storage and handling systems » Electric control and automation



Ottevanger Milling Engineers B.V.

Location: Moerkapelle Moerkapelse Zijde 32 2751 DL MOERKAPELLE The Netherlands Tel. +31 (0)79 593 22 21 Location: Aalten
Dinxperlosestraatweg 62
7122 AH AALTEN
The Netherlands
Tel. +31 (0)543 472 688

Location: Heteren Komkleiland 4 6666 MG HETEREN The Netherlands Tel. +31 (0)26 47 906 99