



OTTEVANGER
MILLING ENGINEERS



Counterflow pellet coolers



General

The Ottevanger Milling Engineers counterflow pellet coolers are used for cooling pellets and expandate to nearly ambient temperature. By drawing air through a product layer the product is cooled.

Single deck cooler

Warm product is continuously fed into the cooling bin through the inlet valve. By drawing air through a product layer which is variable in height the product is cooled. Smooth discharging of cooled product into the outlet hopper is ensured by the discharge system.

Application

- » With electrically driven triple grid discharge system: Cooling of feed pellets, wood pellets, pulp pellets, etc.
- » With hydraulically driven swivel valve discharge system: Cooling of feed pellets, wood pellets, pulp pellets, expandate, full fat soya, etc.

Advantages

- » perfect cooling of the product
- » smooth discharging of cooled product into the outlet hopper
- » total emptying at the end of a run
- » bevelled corners in the outlet hopper to prevent product or fines to pile up



Double deck cooler

As single deck cooler, but in addition; An intermediate deck and the second cooling bin. In normal operation the intermediate deck is open, while the cooler is working like the single deck version. On product change-over, the intermediate deck is closed, just before the new product enters the cooler. The product is then temporarily held on the intermediate deck, while the previous product completes its cooling cycle in the lower cooling bin. Both products are being cooled at the same time. As soon as the lower cooling bin is empty, the intermediate deck opens fully, dropping all product in the lower cooling bin. The intermediate deck now remains open until the next product change.

Application

- » with 2x hydraulically driven swivel valve discharge system: Cooling of feed pellets, wood pellets, pulp pellets, expandate, full fat soya, etc.

Advantages

- » as single deck cooler, but in addition;
- » enables fast change-over between different production runs
- » no need to wait for the cooler to be empty before a new product can be introduced into the cooler

Ottevanger Milling Engineers

Moerkapelle, Aalten and Heteren - The Netherlands
Tel. +31 79 593 22 21
E-mail: info@ottevanger.com

www.ottevanger.com



OTTEVANGER
MILLING ENGINEERS

- » Design » Engineering » Manufacturing » Construction and commissioning
- » Feed mills » Pet food plants » Aqua feed plants » Cereal processing plants
 - » Soybean processing plants » Premix and concentrate plants » Silos
- » Bulk storage and handling systems » Electric control and automation



Ottevanger Milling Engineers B.V.

Location: Moerkapelle
Moerkapelse Zijde 32
2751 DL MOERKAPELLE
The Netherlands
Tel. +31 (0)79 593 22 21

Location: Aalten
Dinxperlosestraatweg 62
7122 AH AALTEN
The Netherlands
Tel. +31 (0)543 472 688

Location: Heteren
Komkleiland 4
6666 MG HETEREN
The Netherlands
Tel. +31 (0)26 47 906 99

www.ottevanger.com
info@ottevanger.com